MTE204

INTRODUCTION TO DATA ANALYSIS IN PYTHON

Scatter Plot	Plot Formats	Histogram	
Bar Graph	·	Pie Chart	

1.0. Introduction to Python 1.1.Why Python

Python is simple and easy to learn, read, and write. It is a Free/Libre and Open Source Software (FLOSS). Meaning one can distribute copies freely, read its source code, modify it, etc. it is a high-level language and portable: meaning it is supported by Linux, Windows, FreeBSD, Macintosh, Solaris, BeOS, OS/390, PlayStation, and Windows CE platforms. Python supports procedure-oriented programming as wells as object-oriented programming. It can also invoke C and C++ libraries can be called from and C++ programs, can integrate with Java and NET components. Python has been used by many of the big companies known today such as: YouTube, Google, Dropbox, RaspberryPi, BitTorrent, NASA and NETFLIX.

Python application includes:

- 1. Web Scrapping
- 2. Automation Testing
- 3. Web Development
- 4. Data Analysis (Our focus in this course)

After the installation of Python, the next step is to start working on python. We will discuss some important attributes then move to data analysis with python.

1.2. What is Data

Data in terms of statistics and probability refers to facts and statistics collected together for reference or analysis. The figure below shows what can generally be done with data.



Data is subcategorized as depicted below:



Quantitative data deals with characteristics and descriptors that cannot be easily measured, but can be observed subjectively.

• Nominal data are data with no inherent order or ranking such as gender or race.



• Ordinal data are data with an ordered series.

Customer ID	Rating
001	Good
002	Average
003	Average
004	Bad

Qualitative data deals with numbers and things that can be measured objectively.

- Discrete data are also known as categorical data; it can hold finite number of possible values e.g. number of student in a class.
- Continuous data are data that can hold infinite number of possible values e.g. a person's weight.

It is worthy to mention here types of variable; which are:

- Discrete variable also known as categorical variable; it can hold values of different categories. For instance, your email can hold value for inbox message or spam message.
- Continuous variable are variables that stores infinite number of values e.g. a vehicle speed.

Hence, variable is anything used to store a value and the kind of data associate with such variable determines if such variable is discrete or continuous.

Variables can either be dependent or independent. Dependent variable are variables whose value depends on any other independent variable.

1.3. Important Attributes

Presented below as some keywords in python

help≻ keyw	words			
Here is a	list of	the Python H	keywords. Enter any	keyword to get more help.
and		elif	if	print
as		else	import	raise
assert		except	in	return
break		exec	is	try
class		finally	lambda	while
continue	8	for	not	with
def	63	from	or	yield
del		global	pass	

1.3.1. Comments

Passing comments in python can be done using the # or *"comment"*. Where there is only one line of comment the # is used. That is any text to the right of # is not executed by python. The *"comment"* is applicable where multiply line of comment is to be passed in python.

Example:

This code analysis a dataset

Or

...

This

Code

Analysis

а

dataset

...

1	# Comment
2	
3	0 ' ' '
4	Bulk Comments
5	Multi-line Comment
6	

Presented below is a demo of the python interface



Figure 1 Character printing

We can see form the Fig. 2 above that the keyword *print* is used to print the character in the string ("") or (") in the brace.



Figure 2 Printing multiply variable form a single line input



Figure 3 Printing multiply variable with comma in print command brace.

1.3.2. Identifier

This is a name used to identify a variable, function, class, module or other object. For instance, in Fig 3 X, Y and Z are identifiers. An identifier can start with A to Z or a to z or an underscore (_) followed by zero or more letters, underscore and digits (0 to

9). Note that python is a case sensitive programming language and does not allow any special character within identifiers such as %, \$ etc.

Identifier Naming Convention

- 1. class name start with an uppercase letter. All other identifier starts with lowercase letter.
- 2. Starting an identifier with one leading underscore means that identifier is private
- 3. Starting an identifier with two leading underscores means that identifier is strongly private
- 4. Ending an identifier with two trailing underscores means that identifier is language-defined special name



Figure 4 identifier

1.3.3. Standard Data Types

Data type is a way of defining what kind of data and entry is; it can be numbers, integer, float, Boolean etc. The data is the entry on the right side of the equality sign and to the left is the identifier. Data can mutable or immutable data type. The figure below presents more details:



Figure 5 Standard Data Type

Immutable Data Type –

1. Numeric Data Type



Spyder (Python 3.6)	– U X	
File Edit Search Source Run Debug Consoles Projects Tools View Help	A	
🗋 🖕 🖹 🐘 🧱 @ 🕨 💾 🛃 🗣 🌾 州 📫 🚝 🐡 🔳 💽 💥 🥕 🥐	← → C:\Users\WCC\.spyder-py3 ~ ► 1	٨.
Editor - C:\Users\WCCspyder-py3\temp.py	× Help &	×
🗅 temp.py 🗵 🔍	🗶 Source Console 🔻 Object 🗸 🖌	Q.
<pre>1 # integer input 2 3 X = 10 4 5 # Float input 6 7 Y = 2.50 8 9 # Complex number input 10 11 Z = 2 + 3j 12 13 print (X, Y, Z) 14</pre>	Usage Here you can get help of any object by pressing Ctrl+I in front of it, either on the Editor or the Console. Help can also be shown automatically after writing a left parenthesis next to an object. You can activate this behavior in <i>Preferences > Help</i> . New to Spyder? Read our <u>tutorial</u>	
15W = 3 - 5j	Variable explorer File explorer Help	
16	IPython console	×
1/print (W -Z)	C Console 1/A 🗵	Ł
19	<pre>In [12]: runfile('C:/Users/NCC/.spyder-py3/temp.py', wdir='C:/Users/NCC/.spyder-py3') 10 HT2204 3 In [13]: runfile('C:/Users/NCC/.spyder-py3/temp.py', wdir='C:/Users/NCC/.spyder-py3') 10 HT2204 3 In [19]: runfile('C:/Users/NCC/.spyder-py3/temp.py', wdir='C:/Users/NCC/.spyder-py3') 10 2.5 (2+3j) In [20]: runfile('C:/Users/NCC/.spyder-py3/temp.py', wdir='C:/Users/NCC/.spyder-py3') 10 2.5 (2+3j) In [20]: runfile('C:/Users/NCC/.spyder-py3/temp.py', wdir='C:/Users/NCC/.spyder-py3') 10 3.5 (2+3j) In [20]: runfile('C:/Users/NCC/.spyder-py3/temp.py', wdir='C:/Users/NCC/.spyder-py3') 10 4.5 (2+3j) In [20]: runfile('C:/Users/NCC/.spyder-py3/te</pre>	~
	T [04].	
	IPython console History log	*
	Permissions: RW End-of-lines: CRLF Encoding: ASCII Line: 19 Column: 1 Memory: 73 %	

2. Sting

The continuous set of characters represented within quotation is called as String. Python allows for either pairs of single or double quotes. Python does not support a character type, these are treated as strings of length one



3. Tuples



Figure 6 Tuples

Mutable Data Type

1. List



Image: Sector Source Num Debug Cublook rules in the source Consider Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 If # List Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 If # List Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 If # List Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 If # List Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 If # List Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 If # List Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 If # List Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3 Image: Cubers/MCCLappeder py3	Spyder (Python 3.6)				- 0	×
Editor -CL/Wars/NCC/Lapydor 0/Sump.py Ø × Help Ø × If # List Source Console ▼ Object V if Ø 1 # List Usarge Usarge Usarge 4 G [3] = 5 Help If Ø List 6 Prinit (Q) B × Here you can get help of any object by pressing CtH+I in front of it, either on the Editor of the Console. Here you can get help of any object by pressing CtH+I in front of it, either on the Editor of the Console. 10 # A List can contain other list as well as tuples at the same time New to Spyder? Read our twarded 11 12P = [Q, 2.45, 'Sola'] New to Spyder? Read our twarded Ø × 13 Here you can get help of any object thy pressing CtH+I in front of it, either on the Editor of the Console. New to Spyder? Read our twarded 13 Here you can get help of any object by pressing CtH+I New to Spyder? Read our twarded Ø × 14 List can contain other list as well as tuples at the same time New to Spyder?Read our twarded Ø × 13 Here you can get help of any object for pressing CtH+I New to Spyder?Read our twarded Ø × 14 Console 16 To console 1	Prie zait search source run bedug Consoles Projects loois view Help P ▷ ▷ □ ▷ □ ▷ □ □ □ □ □ □ □ □ □ □ □ □ □	← → C:\Users	WCC\.spyder-py3		~ 🍃	•
C tempsylic Q Source Conside * Object * C 1 ## List 2 Q [2,5,6,7, 2+4j, 'MTE204'] Here you can get help of any object by pressing CtH+1 In front of it, effection of the Cansole. Here you can get help of any object by pressing CtH+1 In front of it, effection of the Cansole. Here you can get help of any object by pressing CtH+1 In front of it, effection of the Cansole. Here you can get help of any object by pressing CtH+1 In front of it, effection of the Cansole. Here you can get help of any object by pressing CtH+1 In front of it, effection of the Cansole. Here you can get help of any object by pressing CtH+1 In front of it, effection of the Cansole. Here you can get help of any object by pressing CtH+1 In front of it, effection of the Cansole. Here you can get help of any object by pressing CtH+1 In front of it, effection of the Cansole. Here you can get help of any object by pressing CtH+1 In front of it, effection of the Cansole. Here you can get help of any object by pressing CtH+1 In front of it, effection of the Cansole. Here you can get help of any object by pressing CtH+1 In front of it, effection of the Cansole. Here you can get help of any object by pressing CtH+1 In front of it, effection of the Cansole. Here you can get help of any object by pressing CtH+1 In front of it, effection of the Cansole. In front of it, effection of the Cansole. In front of it, effect	Editor - C:\Users\NCC\.spyder-py3\temp.py	< Help				Ξ×
<pre>1# List 2 Q = [2,5,6,7, 2+4j, 'MTE204'] 4 Q = [3,5,6,7, 2+4j, 'MTE204'] 4 Q = [4,5,5,7, 2+4j, 'MTE204'] 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0</pre>	🗅 temp.py 🗵	Source Console 🔻	Object		~ 1	≙ 0.
14 print (P) 15 15 16 dr 17 17 18 Y = [[1,4,5], 2+7j, 'MTE204', 4.67, (1,2,3)] 19 17 19 10 20 print (Y) 21 17 12 17 23 17 24 17 25 17 18 Y = [[1,4,5], 2+7j, 'MTE204', 4.67, (1,2,3)] 19 10 20 print (Y) 21 11 22 11 23 12 24 12 25 11 16 11 17 11 18 12 19 11 10 12 11 12 12 5, 6, 5, (2+4j), 'MTE204'] 12, 5, 6, 5, (2+4j), 'MTE204'] 12, 5, 6, 5, (2+4j), 'MTE204'] 12, 5, 6, 5, (2+4j), 'MTE204'] 12, 5, 6, 5, (2+4j), 'MTE204'] 12, 5, 6, 5, (2+4j), 'MTE204'] 12, 5, 6, 5, (2+4j), 'MTE204'] 12, 5, 6, 5,	<pre>1 # List 2 3 Q = [2,5,6,7, 2+4j, 'MTE204'] 4 Q [3] = 5 6 7 print (Q) 8 9 10 # A list can contain other list as well as tuples at the same time 11 12 P = [Q, 2.45, 'Sola'] 13 14 crit (D)</pre>		Usage Here you can in front of it, Help can also parenthesis i behavior in A	n get help of any object by pressing Ctrl+I either on the Editor or the Console. If the console is a set of the console is the set on object. You can activate this <i>Terferences > Help</i> . New to Spyder? Read our <u>tutorial</u>		
16 ∉ or IPython concole Ø × 17 IA IP III III III III III III III III III IIII IIII IIIIIII IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	15	Variable explorer	File explorer Help			
<pre>1/ 18 Y = [[1,4,5], 2+7j, 'MTE204', 4.67, (1,2,3)] 19 20 print (Y) 21 22 23 24 25 24 25 25 24 25 24 25 24 25 24 25 24 25 25 24 25 24 25 25 24 25 25 24 25 25 24 24 25 24 25 24 24 25 24 24 25 24 24 25 24 24 25 24 24 25 24 24 25 24 24 24 25 24 24 24 24 24 24 24 24 24 24</pre>	16 # or	IPython console	-			đΧ
In [30]: •	1/ 18 Y = [[1,4,5], 2+7j, 'MTE204', 4.67, (1,2,3)] 20 print (Y) 21 22 23 24 25	Console 1,A Console 1,A In (26): runfil [2, 5, 6, 5, 6; In [27]: runfil [2, 5, 6, 5, 6; In [28]: runfil [2, 5, 6, 5, 6; [12, 5, 6, 5, 6; [12, 5, 6, 5, 6; [12, 5, 6, 5, 6; [12, 5, 6, 5, 6; [13, 5, 6, 5, 6; [14, 5], 5, 6, 5, 6;	<pre>3 [1] (C:/Users/NCC/.s 2+4j), 'MTE204'] le('C:/Users/NCC/.s 2+4j), 'MTE204'] (2+4j), 'MTE204'] le('C:/Users/NCC/.s 2+4j), 'MTE204'] (2+4j), 'MTE204'] (2+4j), 'MTE204'] le('C:/Users/NCC/.s 2+4j), 'MTE204'] (2+4j), 'MTE204'] , 'MTE204'], 'MTE204', 4.6</pre>	<pre>spyder-py3/temp.py', wdir='C:/Users/NCC/ spyder-py3/temp.py', wdir='C:/Users/NCC/], 2.45, 'Sola'] spyder-py3/temp.py', wdir='C:/Users/NCC/ 2.45, 'Sola'] spyder-py3/temp.py', wdir='C:/Users/NCC/ 2.45, 'Sola'] 37, (1, 2, 3)]</pre>	<pre>spyder-py3') .spyder-py3') .spyder-py3') .spyder-py3')</pre>	×
IPython console History log		IPython console	History log	1		

Figure 7 List data type

2. Dictionaries

Dictionaries contain key value pairs. Each key is separated from its value by a colon (:), the items are separated by comma, and the whole thing is enclosed within curly braces



Spyder (Python 3.6)	– 01 ×
File Edit Search Source Run Debug Consoles Projects Tools View Help	
🗋 🖕 🖹 🐘 🧱 🖉 🕨 🕼 🖬 📽 🖓 👘 🛠 州 端 🚝 🐎 🔳 💽 💥 🎤 👶	← → C:\Users\WCC\.spyder-py3 ✓ ► ↑
Editor - C:\Users\NCC\.spyder-py3\temp.py 8 ×	Help & X
다. temp.py* 🗵 🗘	, Source Console 🔻 Object 🗸 🖌 🖨 🗞
1 # Dictionaries 2 3 R = { 'Course_code': 'MTE204', 'Class size': 700} 4 5 print (R) 6 7 8 9 10 11 12	Usage Here you can get help of any object by pressing Ctrl+1 in front of It, either on the Editor or the Console. Help can also be shown automatically after writing a left parenthesis next to an object. You can activate this behavior in <i>Preferences > Help</i> . New to Spyder? Read our <u>tutorial</u>
	Variable explorer File explorer Help
	IPython console & X
	Console 1/A 🗵 📃 🍋
	<pre>File C:UserSWRCUMaconasults\site-packages\spyder\utils\site\siteCustomize.py ,</pre>
	In [32]:
	Permissions: RW End-of-lines: CRLF Encoding: ASCII Line: 6 Column: 1 Memory: 77 %

Figure 8 Dictionaries

You can have dictionary within a dictionary or any other combination of data types.

3. Sets





Figure 9 Sets

1.3.4. Operators

Operators are important in the execution of operation in python. Fig 11 below presents operators in python.

Operators



1. Arithmetic Operators



2. Assignment Operator



3. Comparison Operator

Equal To	a == b
Not Equal To	a != b
Greater Than 📥	a > b
Less Than	a < b
Greater Than Equal To 📄	a >= b
Less Than Equal To 🛛 🛶	a <= b

Spyder (Python 3.6)	– o ×
File Edit Search Source Run Debug Consoles Projects Tools View Help	
🗅 🖕 🖹 🐘 💷 🖉 🕨 🔛 💭 🗣 📜 🖬 🔀 🏏 🌾	🕨 🗲 🄶 C:\Users\WCC\.spyder-py3 🗸 🖉 🛧
Editor - C:\Users\NCC\.spyder-py3\temp.py	S × Help S ×
🗀 temp.py 🔀	🗞 Source Console 🔻 Object 🗸 🖌 🏠
1 # Sets 2 3 K = {1,3,5,6,7,7,7,8,9} 4 5 print (K) 6 a,b = 2,5 7 D=a==b 8 print (D) 9 J = a!=b 10 print (J) 11 C = bya 12 print (C)	Usage Here you can get help of any object by pressing Ctrl+I in front of it, either on the Editor or the Console. Help can also be shown automatically after writing a left parenthesis next to an object. You can activate this behavior in <i>Preferences > Help</i> . New to Spyder? Read our <u>Lutorial</u>
13	
14 15 16 17 18 19 20 21 22	Variable explorer File explorer Help Python console C console 1/A False True True In [40]:
	,
	IPython console History log
	Permissions: RW End-of-lines: CRLF Encoding: ASCII Line: 13 Column: 1 Memory: 77 %

4. Logic Operators



5. Bitwise Operator



6. Identity Operator





Figure 10 Identity operator

7. Membership Operator: works on list, dictionary and tuples to check if an element exist within any of those.





Figure 11 Membership

2.0. Data Analysis with Python

This is the process of inspecting, cleaning, transforming, and modeling data with the goal of discovering useful information's, suggesting conclusions and supporting decision making.



Figure 12 Data life cycle

Python provides various methods for data analysis, manipulation (NumPy and Pandas libraries) and visualization (Matplotlib library) (see Fig 14).



Figure 13 Data Analysis in Python

2.1. Introduction to NumPy Library

NumPy is a package for scientific computing in Python. NumPy features is presented in Fig. 15 and operations in NumPy is presented Fig. 16.



Figure 14 NumPy Features



Figure 15 Operations in NumPy

NumPy has an array called ndarray; is is a multidimensional array object of two parts-the actual data, some metadata which describes the stored data. They are indexed just like sequences are in Python, starting from 0



Each element in ndarray is an object of data-type object called *dtype*. An item extracted from ndarray, is represented by a Python object of an array scalar type (Please note that this done internally by Python).



2.1.1. Creating a NumPy Array

The NumPy is a library in Python therefore, the first step is to import the NumPy library. See Fig 17.



Figure 16 creating NumPy Array

The linspace function in Python can allow us to create a vector by calling the linspece function in NumPy and specifying the initial, final and the step. See Fig. 18.



Figure 17 Linspece function

2.1.2. Creating a Multidimensional NumPy Array

Import the NumPy library as np (as in Fig 17) and pass the array code as seen in Fig. 19.



Figure 18 Multidimensional NumPy Array

The arrange function can also be used to create a multidimensional array within a specified range. See Fig. 20.

Spyder (Python 3.6)	– U X
File Edit Search Source Run Debug Consoles Projects Tools View Help	
└`┣ 🖹 🐁 🗮 @ 🕨 🗗 🕶 🗣 🔰 🖬 🗳 🖬 🛸 🔛 💥	C: Users WCC spyder-py3
Editor - C:\Users\NCC\.spyder-py3\temp.py	8 × Help 8 ×
🗀 temp.py* 🗵	🗞 Source Console 🔻 Object 🗸 🖌 🕯
1 # NumPy 2 3 # Nultidimensional Array using arange function 4 5 import numpy as np 7 0 = np.arange(0,1000) 8 print (D) 10 11 12 13	Usage Here you can get help of any object by pressing Ctrl+1 in front of it, either on the Editor or the Console. Help can also be shown automatically after writing a left parenthesis next to an object. You can activate this behavior in Preferences > Help. New to Spyder? Read our tutorial
	Variable explorer File explorer Help
	IPython console & X
	Console 1A Image: Console 1A <th< th=""></th<>
	Permissions: RW End-of-lines: CRLF Encoding: ASCII Line: 9 Column: 1 Memory: 71%

Figure 19 Arange function

We can also create an array of zeros by using the zeros function and specifying the number of rows and column. See Fig. 21

Spyder (Python 3.6)	– 0 ×	
File Edit Search Source Run Debug Consoles Projects Tools View Help		
🗋 🖕 🖹 🔚 @ 🕨 🛃 🗗 🗭 州 端 🚝 🇭 📕 🖼 🏹 🎤 🤚	← → C:\Users\VCC\.spyder-py3 ~ ► 1	
Editor - C: \Users \NCCspyder-py3\temp.py & X	< Help &	×
🗅 temp.py 🗵 🌼	🕻 Source Console 🔻 Object 🔍 🖕	¢.
<pre># NumBy # NumBy #</pre>	Usage Here you can get help of any object by pressing Ctrl+1 in front of it, either on the Editor or the Console. Help can also be shown automatically after writing a left partnesis next to an object. You can activate this behavior in <i>Preferences > Help</i> . New to Spyder? Read our tutorial Python console Image: Console 1/A Solution (Console 1/A Solution (Con	× * *
	Permissions: RW End-of-lines: CRLF Encoding: ASCII Line: 3 Column: 46 Memory: 72 %	

Figure 20 Array of zeros

2.1.3. Creating an Array from Existing Data

The numpy.asarray is used converting Python sequence into ndarrays.

- Syntax numpy.asarray(a, dtype = None, order = None)
- The following piece of code converts a python list into an array



Figure 21 Creating an Array from Existing Data

2.1.4. Restructuring a NumPy Array

A linear array of any number of elements can be restructured as desired. Here will make an instance, converting a linear array of 8 elements into $2 \times 2 \times 2$ 3D array consider the case of transpose in matrix.





Figure 22 Restructuring a NumPy Array

The restructured array can be returned to its initial state by using the function ravel.



Figure 23 using the ravel function

2.1.5. Indexing a NumPy Array

Indexing in NumPy array is identical to Python's indexing scheme



Figure 24 Indexing NumPy Array

Slicing a NumPy array, the slice object is constructed by providing the initial, final and the step parameter to slice ()



Figure 26 Indexing and Slicing of NumPy Array

Other slicing method possible in Python is presented in Fig.28





NumPy array attributes can be derived by following the step in Fig. 29



Figure 28 NumPy Array Attributes

2.1.6. Reading and writing from files 2.1.6.1.Reading and Writing from Text file

NumPy provides the option of importing data from files directly into ndarray using the loadtxt function. The savetxt function can be used to write data from an array into text file.



Spyder (Python 3.6)						- 0	×
File Edit Search Source Run Debug Consoles Projects Tools View Help							
🗋 🖕 🖹 🐁 🗮 🖉 🕨 🛃 🕪 🗲 州 端 🚝 🐡 📕 🛽	E 🗙 🗡 🔶	← → C:\Users\WCC\	.spyder-py3			~ 🗲	• •
Editor - C:\Users\NCCspyder-py3\temp.py	8×	File explorer					ēΧ
🗅 temp.py* 🗵 test.txt 🗵	0.	000					Q.
1 # Reading and writing into file		Name	Size	Туре	Date Modified		^
3 import numpy as np		> 🗁 defaults		File Folder	9/2/2019 5:11 PM		
4		> 🗁 plugins		File Folder	9/2/2019 5:11 PM		
5 X = np.arange(20)		> 🗁 spyder.lock		File Folder	9/19/2019 11:02 AM		
6 7 point (X)		history_internal.	py 08 bytes	py File	9/19/2019 11:03 AM		
princ (x)		i≣ history.py	530 bytes	py File	9/19/2019 11:08 AM		
9 #Writing into a text file		langconfig	2 bytes	File	9/2/2019 5:10 PM		
10 np.savetxt('test.txt',X)		onlinehelp	0 bytes	File	9/5/2019 12:39 PM		
11		spyder.ini	21 KB	ini File	9/19/2019 11:04 AM		
12 #Keading from a text file		spyder.ini.bak	21 KB	bak File	9/19/2019 11:06 AM		
14 print (Y)		i≣ temp.py	114 bytes	py File	9/19/2019 1:09 PM		
		i template.py	51 bytes	py File	9/2/2019 5:11 PM		
		i test.txt	500 bytes	txt File	9/19/2019 1:09 PM		
		workingdir	38 bytes	File	9/19/2019 1:09 PM		
		Variable explorer File	explorer Help				*
		IPython console					8×
		🗅 Console 1/A 🗵					Q.
		File "C:/Users/N X = np.arang(2)	CC/.spyder-py3/te 0)	mp.py", line	≥ 5, in <module></module>		^
		AttributeError: mo	dule 'numpy' has	no attribute	'arang'		
		In [42]:					
		In [42]: runfile('	C:/Users/NCC/.spy	der-py3/temp	o.py', wdir='C:/Users/NCC/.	spyder-py3')	
		[0 1 2 3 4 5	6 7 8 9 10 1	der-py3/temp 1 12 13 14 1	.py', wdir='C:/Users/NCC/. L5 16 17 18 19]	spyder-py3')	
		[0. 1. 2. 15. 16. 17. 1	3. 4. 5. 6. 8. 19.]	7. 8.	9. 10. 11. 12. 13. 1	4.	
		In [44]:					~
		IPython console Histe	ory log				
		Permissions: RW En	nd-of-lines: CRLF	Encoding: ASCI	II Line: 14 Column: 1	0 Memory: 74	4 %

Figure 29 Writing and Reading from a Text file

2.1.6.2.Reading and Writing from CSV file

NumPy arrays can be dumped into CSV using the savetxt and the comma delimiter and the CSV file can be read into NumPy array using the genfromtxt function.



Source (Puthon 3.6)					- 7	×
File Edit Search Source Run Debug Consoles Projects Tools View Help						
	B 🗙 🗡 🐥	← → C:\Users\WCC\.	spyder-py3		~ 🗲	• •
Editor - C:\Users\NCC\.spyder-py3\temp.py	8×	File explorer				ēΧ
🗅 temp.py 🗵 test.txt 🗵 test.csv 🗵	0.	000				Q.
<pre>L: tempsy & testatt & testary & 1 # Reading and writing into CSV file 3 import numpy as np 4 # Create a multidimensional array X 6 # Create a multidimensional array X 6 # write to CSV file 11 np.savetxt('test.csv', X, delimiter=',') 12 13 14 #Load from CSV file 15 P = np.genfromtxt{'test.csv', delimiter=',') </pre>	0	Name Name Name > b defaults > b plogins > b syder.lock inistory.internal, plansing > history.internal, plansing > history.internal, plansing > onlinehelp > spyder.lock Itemp.py > temp.py > tett.csv > test.csv > test.txt > workingdir Yariable explorer > Python console In [54]: runfile(`C [1 [54]: runfile(`C [2 3 4] [6 7 8]] In [55]:	Size Type File Folder File Folder File Folder Site Yorks py File 2 bytes File 2 bytes File 2 tytes File 2 tytes File 2 tytes File 2 tytes File 2 tytes ty File 3 bytes py File 3 bytes py File 3 bytes ty File 3 bytes ty File 3 bytes ty File 2 bytes ty File 3 bytes ty File 2 bytes ty File 3 bytes ty File 2 bytes file 2 b	Date Modified 9/2/2019 5:11 PM 9/2/2019 5:11 PM 9/19/2019 1:02 AM 9/19/2019 1:03 AM 9/19/2019 1:03 AM 9/2/2019 5:10 PM 9/2/2019 1:03 PM 9/19/2019 1:06 PM 9/19/2019 1:06 PM 9/19/2019 1:16 PM 9/19/2019 1:15 PM 9/19/2019 1:09 PM	pyder-py3*)	Q. (1)
		Permissions: RW En	d-of-lines: CRLF Encoding: AS	CII Line: 15 Column: 45	Memory: 7	8%

Figure 30 Writing and Reading from CSV file

2.2. Introduction to Pandas Library

Pandas is an open-source Python library which provides efficient, easy-to-use data structure and data analysis tools. Pandas is built on NumPy and the name Pandas is derived from "Panel Data" = an Econometrics form multidimensional data. The Pandas library is well suited for several kind of data like:

- 1. Tabular data with heterogeneously-typed columns
- 2. Ordered and unordered time series data.
- 3. Arbitrary matrix data with row and column labels
- 4. Any other form of observational / statistical data sets. The data actually need not be labeled at all to be placed into Pandas data structure

2.2.1. Data Structure in Pandas

Pandas provides three data structures; Series, DataFrames, Panels all to which are built on NUmPy array. Note all data structure in Pandas are value-mutable.

Data Structure	Dimension	Description
Series	1	Labeled, homogenous array of immutable size
DataFrames	2	Labeled, heterogeneous typed, size-mutable tabular data
		structure
Panels	3	Labeled size-mutable array

2.2.1.1. Series

Series is a single dimensional array structure that stores homogenous data i.e., data of single type. All element in the Series are value-mutable but size-immutable.

Data	Can be of multiple data types such as ndarray, lists, constants, series, dict etc.
Index	Indexes must be unique, hashable and have the same length as data Defaults to np.arrange(n) if no index is passed
dtype	Data type of each column; If none is mentioned, it will be inferred; automatically
сору	Deep copies data, set to false as default

Fig. 31 presents the creation of a Series using the Pandas library.



Figure 31 Creating Series Using Pandas Library in Python

We can see from the output console in Fig. 31 that Python automatically added the default index for the data. However, we can set the index by using the dictionary data structure to input the Series. See Fig 31.

Elements within a Series can be accessed using the slicing function as earlier stated in Fig. 27 and 28 however, an example is provided in Fig. 32.



Figure 32 Accessing Data in Series Using Slicing

2.2.1.2.DataFrames

DataFrames is a 2D data structure in which data is aligned in tabular fashion consisting of rows and columns.



Fig. 33 shows how DataFrame is created. We will notice that Python automatically printed the default index as in the case of Series and a default column name of 0. We can input our own column name by using a dictionary to input the data.



Figure 33 Creating DataFrame



Figure 34 The NaN case

We can also specify our own index see Fig. 35

							-		~
Spyder (Python 3.6)							– u		~
File Edit Search Source Run Debug Consoles Projects Tools View Help									
	EX 🗡 🤻		← → C:\Users\WCC\.s;	pyder-py3			~		1
Editor - C:\Users\NCC\.spyder-py3\temp.py		5 ×	File explorer						δ×
C temp.pv* 🗙 test.txt 🖾 test.csv 🖾		ø	000						Q.
<pre>1 # Introduction to Pandas 2 3 4 import pandas as pd 5 6 A = ([2,3,4,5,6,7]) 7 7 B = pd.DataFrame(A) 9 print (B) 10 11 12 # using a list of dictionaries to input data in DataFrame 13 </pre>		-	Name > defaults > plugins > spyder.lock inistory.internal.py history.py langconfig onlinehelp spyder.ini pyder.ini.bak	Size	Type File Folder File Folder File Folder 58 bytes py File 26 bytes py File 2 bytes File 0 bytes File 21 KB ini File 21 KB bak File 14 byter er Sile	Date Modified 9/2/2019 5:11 PM 9/12/2019 1:102 AM 9/19/2019 11:02 AM 9/19/2019 11:03 AM 9/2/2019 5:10 PM 9/2/2019 5:10 PM 9/19/2019 11:04 AM 9/19/2019 11:06 AM			^
<pre>14 G = [{'Naths':60, 'Biology': 80, 'Chemistry': 70, 'Physics':45}, {'Maths': 45, 15 # inputing your own index 17 D = pd.DataFrame(G, index=['John', 'David']) 18 print (D) 19 20</pre>	'Biology': 65,	9 	temp.py template.py test.csv test.tst workingdir Variable explorer File e	1 5 explorer	14 bytes py File 81 bytes py File 50 bytes csv File 00 bytes txt File 38 bytes File Help	9/19/2019 1:09 PM 9/2/2019 5:11 PM 9/19/2019 1:37 PM 9/19/2019 1:15 PM 9/19/2019 1:09 PM			*
			IPython console						₽×
			Console 1/A 🗵						Q.
			In [67]: 0 0 1 3 2 4 5 7 Biology Cher David 65 In [68]:	:/Users/N mistry M 70 70	CC/.spyder-py3/tem aths Physics 60 45.0 45 NaN	p.py', wdir='C:/Users/NC	C/.spyder-py3	3.)	~
<		>	IPython console Histor	ry log					
	M	ovies	& TV ssions: RW End	l-of-lines: C	RLF Encoding: ASC	II Line: 16 Colum	n: 26 Memory:	79 9	%

Figure 35 Using your own Index in Data Frame

Series can be converted to DataFrame see Fig. 36

Spyder (Python 3.6)							- 0	×
File Edit Search Source Run Debug Consoles Projects Tools View Help								
🗅 🖕 🖻 🐁 🗮 @ 🕨 🖽 🖬 🗳 🖌 🖌 🗮 🗮 📕	🗄 🔀 🎤 🍦	+	C:\Users\WCC\.s	spyder-py3			~ 2	• •
Editor - C:\Users\NCC\.spyder-py3\temp.py	8	× Fi	e explorer					ēΧ
🗅 temp.py 🗵 test.txt 🗵 test.csv 🗵		O G	00					Q.
<pre>I tempory & testor() testor() If Introduction to Pandas A taport pandas as pd f a create the Series 7 8 Series1 = pd.Series([80, 70, 60, 45], index= ['Biology', 'Chemistry', 'Maths', 9 Series2 = pd.Series([60, 59, 80, 65], index= ['Biology', 'Chemistry', 'Maths', 10 12 # Convert the Series to DataFrame 13 14 Table = pd.DataFrame(('John':Series1, Femi':Series2)) 13 16 print (Table)</pre>	'Phyiscs']) 'Phyiscs'])	C C C C C C C C C C C C C C C C C C C	Ame defaults pugins spydet.lock history.internal.pp chistory.pm angconfig onlinehelp onlinehelp onlinehelp onlinehelp onlinehelp onlinehelp onlinehelp temp.pr temp.pr temp.pr temp.sc	Size y 6 53 53 11- 13- 50 3 explorer H :/Users/NC hn 80 70 60 45	Type File Folder File Folder File Folder Bytes py File Dottes File 21KB ini File 21KB ini File 21KB bak File 40ytes py File Dottes cy File Dottes cy File Dottes cy File Dottes cy File Dottes cy File C/.spyder-py3/tem	Date Modified 9/2/2019 5:11 PM 9/2/2019 5:11 PM 9/1/2/2019 1:102 AM 9/1/9/2019 1:103 AM 9/2/2019 1:104 AM 9/2/2019 1:104 AM 9/1/9/2019 1:104 AM 9/1/9/2019 1:104 AM 9/1/9/2019 1:104 AM 9/1/9/2019 1:109 PM 9/1/9/2019 1:37 PM 9/1/9/2019	'.spyder-py3' '.spyder-py3'	• • • • • • • • • • • • • • • • • • •
			Python console Histor	ry log			-	70.04
		Pe	missions: RW End	1-of-lines: CR	LF Encoding: ASC	II Line: 14 Column:	39 Memory:	/9%

Figure 36 Converting Series to DataFrame

Column addition and deletion is possible with DataFrame

1. To add column to a DataFrame the data must be passed as Series

🗋 🖕 🕾 🐁 🗮 @ 🕨 🛃 📭 🗲 州 端 🚝 🔶 📕 🛽	E X /	e	← → C:\Users\WCC	\.spyder-py3			~ 🍃	•
Editor - C:\Users\NCCspyder-py3\temp.py		₽×	File explorer					đΧ
🗅 temp.py* 🗵 test.txt 🗵 test.csv 🗵		Q.	000					Q.
<pre>1# Introduction to Pandas 2 3 4 import pandas as pd 5 6# create the Series 8 Series1 = pd.Series([80, 70, 60, 45], index= ['Biology', 'Chemistry', 'Maths', 9 Series2 = pd.Series([60, 50, 80, 66], index= ['Biology', 'Chemistry', 'Maths', 11 12# Convert the Series to DataFrame 13 Table = pd.DataFrame({'John':Series1, 'Femi':Series2}) 14 Table = pd.DataFrame({'John':Series1, 'Femi':Series2}) 15 # Adding a new Column 13 Table['Seyi'] = pd.Series([30, 69, 67, 78], index=['Biology', 'Chemistry', 'Mat 20 print (Table)</pre>	'Phyiscs']) 'Phyiscs']) ths', 'Phyisc	s'])	Name Name Mame Manuel Name Manuel Name Name Name Name Name Name Name Spyder.lock Spyder.lock Spyder.ini.bak Temp.py Hemplate.py Meticsv Test.tov Mattase Spyten console Console 1/A Sillogy Generative Name	Size py 68 bytes 2 bytes 0 bytes 0 bytes 0 bytes 0 bytes 2 bytes 0 bytes 14 bytes 114 bytes 50 bytes 500 bytes 38 bytes 500 bytes 38 bytes 30 bytes 30 bytes 45 78 78	Type Type Tile Folder File Folder File Folder py File py File bak File py File tot File tot File tot File der-py3/temp.	Date Modified 9/2/2019 5:11 PM 9/12/2019 5:11 PM 9/19/2019 11:02 AM 9/19/2019 11:02 AM 9/19/2019 11:03 AM 9/19/2019 11:06 AM 9/19/2019 11:06 AM 9/19/2019 11:06 AM 9/19/2019 11:06 PM 9/19/2019 11:06 PM 9/19/2019 11:07 PM 9/19/2019 11:07 PM 9/19/2019 11:09 PM 9/19/2019 11:09 PM	[] [/.spyder-py3*]	 ↓ ↓

Figure 37 Adding a Column to a DataFrame

2. Deleting a Column from a DataFrame is done by using the del function • Spyder (Python 3.6)

Spyder (Python 3.6)			- 0 ×	
File Edit Search Source Run Debug Consoles Projects Tools View Help				
🗋 🖕 🖹 🐘 🧱 🖉 🕨 🛃 🔂 🖬 📽 💭 💭 💭 🗮 🔚 💽	S 🗡 🤻		C:\Users\WCC\.spyder-py3	Þ.
Editor - C:\Users\NCC\.spyder-py3\temp.py	ė	5 ×	5 × File explorer 5	×
🗀 temp.py 🛛 test.txt 🖾 test.csv 🖾		Q.		Q,
<pre>i # Introduction to Pandos i # Introduction to Pandos i # Introduction to Pandos i # Create the Series f # Create the Series f # Convert the Series[[60, 90, 60, 45], index= ['Biology', 'Chemistry', 'Naths',</pre>	'Phyiscs']) Phyiscs']) hs', 'Phyiscs']])	Name Size Type Date Modified > © defaults File Folder 9/2/2019 \$111 PM > © plugins File Folder 9/2/2019 \$111 PM > © spyder.lock File Folder 9/2/2019 \$110 AM @ history.internal.py 68 bytes py File 9/19/2019 11:02 AM @ history.internal.py 68 bytes py File 9/19/2019 11:08 AM @ history.internal.py 56 bytes py File 9/2/2019 51:0 PM @ ningconfig 2 bytes File 9/2/2019 11:08 AM @ ningconfig 2 bytes File 9/2/2019 11:08 AM @ spyder.ini.ak 21 KB ini File 9/19/2019 11:08 AM @ spyder.ini.ak 21 KB ini File 9/19/2019 11:09 PM @ template.py 11 4 bytes py File 9/19/2019 11:09 PM @ tetc.ov 150 bytes cov File 9/19/2019 11:09 PM @ tett.ov 150 bytes cov File 9/19/2019 11:37 PM @ tetc.ov 150 bytes cov File 9/19/2019 11:39 PM In tetc.ov 150 bytes cov File 9/19/2019 11:39 PM In tetc.ov 150 bytes cov File 9/19/2019 11:39 PM In tetc.ov 150 bytes cov File 9/19/2019	< > × 22 <
٢		>	> IPython console History log	
			Permissions: RW End-of-lines: CRLF Encoding: ASCII Line: 22 Column: 2 Memory: 74 %	

Figure 38 Deleting a Column from a DataFrame

3. We can also use the pop function to view on the column of interest. For instance, let view the result of Femi only

😵 Spyder (Python 3.6)	- 0	×
File Edit Search Source Run Debug Consoles Projects Tools View Help		
🗅 🖕 🖻 🐂 🧱 🕐 🕨 🔛 🚱 🗣 🗳 👘 🛠 🖊 📫 💭 🛠 🎸 🍊	👂 🗲 🔶 C:\Users\WCC\.spyder-py3 🔷 📂	$\mathbf{\Phi}$
Editor - C:\Users\WCC\.spyder-py3\temp.py	B × File explorer	ðΧ
🗀 temp.py 🔀 test.txt 🖾 test.csv 🖾	000	Q.
<pre>temp.py test.tet t test.cav t test.c</pre>	C C O Name Size Type Date Modified Name Size File Folder 9/2/2019 5:11 PM > Supdation File Folder 9/2/2019 1:02 AM > Supdation File Folder 9/2/2019 1:02 AM > Supdation File Folder 9/19/2019 1:03 AM > Initiony_internal.pv 68 bytes py File 9/19/2019 1:03 AM Diangconfig 2 bytes File 9/19/2019 1:03 AM Considering 2 bytes File 9/19/2019 1:03 AM Sypder.nin 21 KB ini File 9/19/2019 1:06 AM Sypder.nin 21 KB ini File 9/19/2019 1:06 AM Sypder.nin 21 KB ini File 9/19/2019 1:06 PM Considered Sypder.nin 21 KB ini File 9/19/2019 1:03 PM Sypder.nin 21 KB ini File Sypder.nin 21 KB ini File 9/19/2019 1:03 PM Console IA Stop tes to File 9/19/2019 1:03 PM Console IA Stop test to File 9/19/2019 1:09 PM Variable explorer Help Python console Python console Stop test fi	& ^ ^ → → → → → → → → → → → → → → → → →
29 30	Phylacs 65 Name: Femi, dtype: int64 In [93]:	
		*
٢	> IPython console History log	
	Permissions: RW End-of-lines: CRLF Encoding: ASCII Line: 23 Column: 30 Memory: 86	%

Figure 39 Using the pop function

Row addition and deletion is possible with DataFrame

1. Rows can be selected in DataFramenby passing the row label to the loc[] function. Alternatively, we can pass in the row index into the iloc[] function.

<pre>File Life Sarch Source Run Debug Concoles Pojects Tools View Help File Life Sarch Source Run Debug Concoles Pojects Tools View Help File Sarch Source Run Debug Concoles Pojects Tools View Help File Sarch Source Run Debug Concoles Pojects Tools View Help File Sarch Source Run Debug Concoles Pojects Tools View Help File Sarch Source Run Debug Concoles Pojects Tools View Help File Sarch Source Run Debug Concoles Pojects Tools View Help File Sarch Source Run Debug Concoles Pojects Tools View Help File Sarch Source Run Debug Concoles Pojects Tools View Help File Sarch Source Run Debug Concoles Pojects Tools View Help File Sarch Source Run Debug Concoles Pojects Tools View Help File Sarch Source Run Debug Concoles Pojects Tools View Help File Sarch Source Run Debug Concoles Pojects Tools View Help File Sarch Source Run Debug Concoles Pojects Tools View Help File Sarch Source Run Debug Concoles Pojects Tools View Help File Sarch Source Run Debug Concoles Pojects Tools Pojects Pojects Pojects Pojects Tipe Pojects Pojec</pre>	😵 Spyder (Python 3.6)					– 0 ×
Image: The set of the series	File Edit Search Source Run Debug Consoles Projects Tools View Help					
Educ - Clisory MCL spyder py 3 lamp.py Ø × File explore Ø × Import Lattit Lettor Explore Ø × Import Lattit Lettor Explore Ø × Import Lattit Lettor Ø × Ø × Ø × Import Lattit Lettor Ø × Ø × Ø × Ø × Import Lattit Lettor Ø × Ø × Ø × Ø × Import Lattit Lettor Ø × Ø × Ø × Ø × Import Lattit Lettor Ø × Ø × Ø × Ø × Ø × Import Lattit Lettor Ø ×	🗅 🖕 🖻 🐂 🧰 🖉 🕨 🛃 🐏 🛠 州 📫 🚝 🔶 🔳 💌 🗙	ڂ عر	← → C:\Users\WCC\.sp	yder-py3		
Import Textoduction to Pundos Import Size Type Det Modified Ame 1 # Introduction to Pundos Import Berless Size Type Det Modified Ame 3 # Scriets the Series Size Type Det Modified Ame 3 # Scriets the Series Size Size Type Det Modified Ame 3 # Scriets the Series Size Size Fielder 9/22019 S11 PM Biotopuictenality	Editor - C:\Users\NCC\.spyder-py3\temp.py	8×	File explorer			8×
<pre>A size time to Pandas series1 = pd.Series([00, 70, 60, 45], indexe ['Biology', 'Chemistry', 'Naths', 'Phylics']) series1 = pd.Series([00, 70, 60, 45], indexe ['Biology', 'Chemistry', 'Naths', 'Phylics']) series2 = pd.Series([00, 50, 80, 80, 55], indexe ['Biology', 'Chemistry', 'Naths', 'Phylics']) series2 = pd.Series([00, 50, 80, 80, 55], indexe ['Biology', 'Chemistry', 'Naths', 'Phylics']) series2 = pd.Series([00, 50, 80, 80, 55], indexe ['Biology', 'Chemistry', 'Naths', 'Phylics']) series2 = pd.Series([00, 50, 80, 80, 55], indexe ['Biology', 'Chemistry', 'Naths', 'Phylics']) series2 = pd.Series([00, 50, 80, 80, 55], indexe ['Biology', 'Chemistry', 'Naths', 'Phylics']) series2 = pd.Series([00, 50, 70], indexe ['Biology', 'Chemistry', 'Naths', 'Phylics']) series2 = pd.Series([00, 50, 70], indexe ['Biology', 'Chemistry', 'Naths', 'Phylics']) series2 = pd.Series([00, 50, 70], indexe ['Biology', 'Chemistry', 'Naths', 'Phylics']) series2 = pd.Series([00, 50, 70], indexe ['Biology', 'Chemistry', 'Naths', 'Phylics']) series2 = pd.Series([00, 60, 67, 70], indexe ['Biology', 'Chemistry', 'Naths', 'Phylics']) series2 = pd.Series([00, 60, 67, 70], indexe ['Biology', 'Chemistry', 'Naths', 'Phylics']) series2 = pd.Series([00, 60, 67, 70], indexe ['Biology', 'Chemistry', 'Naths', 'Phylics']) series2 = pd.Series([00, 60, 67, 70], indexe ['Biology', 'Chemistry', 'Naths', 'Phylics']) series2 = pd.Series([00, 60, 67, 70], indexe ['Biology', 'Chemistry', 'Naths', 'Phylics']) series2 = pd.Series([00, 60, 67, 70], indexe ['Biology', 'Chemistry', 'Naths', 'Phylics']) series2 = pd.Series([00, 60, 67, 70], indexe ['Biology', 'Chemistry', 'Naths', 'Phylics']) series2 = pd.Series([00, 60, 67, 70], indexe ['Biology', 'Chemistry', 'Naths', 'Phylics']) series2 = pd.Series([00, 60, 67, 70], indexe ['Biology', 'Chemistry', 'Naths', 'Phylics']) series2 = pd.Series([00, 60, 67, 70], indexe ['Biology', 'Chemistry', 'Naths', 'Phylics']) series2 = pd.Se</pre>	🗅 temp.py* 🗵 test.txt 🗵 test.csv 🗵	Q	000			Q.
C Eviten console History log	<pre>i defut(s) defut</pre>	s']) s']) hyiscs'])	Name Name defaults de	Size Type File Folder File Folder File Folder Site Solves py File Site Solves py File Site Solves File 2 bytes File 2 bytes File 2 bytes File 2 bytes File 3 bytes py File Site Sov File Sit	Date Modified 9/2/2019 5:11 PM 9/19/2019 1:102 AM 9/19/2019 1:103 AM 9/19/2019 1:103 AM 9/2/2019 1:104 AM 9/2/2019 1:209 PM 9/2/2019 1:209 PM 9/19/2019 1:104 AM 9/19/2019 1:104 AM 9/19/2019 1:109 PM 9/2/2019 1:15 PM 9/19/2019 1:15 PM 9/19/2019 1:37 PM	5 × 5 × 2(.spyder-py3')
Permissions: RW End-of-lines: CRLF Encoding: ASCT1 Line: 24 Column: 1 Memory 78%			Permissions: RW End	-of-lines: CRLE Encoding:	ASCII Line: 24 Colum	n: 1 Memory: 78 %

Figure 40 Using the loc function for row selection

2.2.2. Importing and Exporting data using Pandas

Data can be loaded into DataFrame from input data stored in CSV format using the read_csv() function



- 1. Create a CSV file in Python
- 2. Then read the file

😵 Spyder (Python 3.6)								- 0	×
File Edit Search Source Run Debug Consoles Projects Tools View Help	e	•	← → C:\Users\V	ICC\.spyder-	руЗ			~	• •
Editor - C:\Users\NCC\.sovder-ov3\temp.ov	<i>5</i> ×	×	File explorer						<i>5</i> >
🗅 temp.py 🗵 test.txt 🗵 test.csv 🗵 Pandas.csv 🗵	0	æ	000						0
<pre>1 # Introduction to Pandas 2 3 4 import pandas as pd 5 6 # Reading CSV file in Pandas 7 7 8 Table = pd.read csv('Pandas.csv') 9 10 print(Table) 11 14 14 15 16 </pre>			Name Name Name Name Name Name Name Name	Size Size Fle explore schule ' e('C:/Use SS SS SS SS SS SS SS SS SS SS SS SS SS	r Help	<pre>fype file Folder ile Folder ile Folder ile Folder ile Folder y File ile sv File y File y</pre>	Date Modified 9/2/2019 5/12 PM 9/2/2019 5/16 PM 9/2/2019 5/16 PM 9/2/2019 5/16 PM 9/2/2019 5/16 PM 9/19/2019 11:02 AM 9/19/2019 11:02 AM 9/19/2019 11:02 AM 9/19/2019 11:08 AM 9/19/2019 11:08 AM 9/19/2019 1:06 AM 9/19/2019 1:06 AM 9/19/2019 1:06 AM 9/19/2019 1:06 PM 9/19/2019 5:01 P	spyder-py3*)	6 ×
			Permissions: RW	End-of-li	nes: CRLF	ncoaing: AS	Line: 8 Column: 1	6 Memory: /	5 %

Figure 41 Reading CSV file to Pandas Library

Data present in a given DataFrame can be written to CSV file using the to_csv() function. If the specified path does not exist, a file of the same name is automatically created.

	ر	Path to
NCT 44 York He spectra to Water and Andread States Man and Andread States He shared States to		
Internet processor and and the second of the		
In the spectral sector (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)		CSV
19. Ben gan and the second sec		

Similarly, we can write to and read from excel file using Pandas



Figure 42 Reading from Excel file



Figure 43 Writing to Excel file

2.3. Introduction to Data Visualization and Matplotlib

Matplotlib is a Python library specifically designed for development of graphs, charts etc., in order to provide interactive data visualization.

2.3.1. Plotting in Matplotlib

Plotting ins Python is done by importing the matplotlib.pyplot library as plt and pass in the argument.



Figure 44 Using Matplotlib Library in Python

A	-	~
Spyder (Python 3.6)	– D	^
	← → C:\Users\WCC\.spyder-py3 \	- T
Editor - C:\Users\NCC\.spyder-py3\temp.py 8 >	File explorer	8 ×
🗅 temp.py* 🗵 test.txt 🗵 test.csv 🗵 Pandas.csv 🗵	000	Q.
Import test.ov Pandas.cov C I # Plotting using Matplotlib I amport matplotlib.pyplot as plt # umcon specify x and y values and plot Y Values = [2,4,5,6,7] Y Values = [4,7,9,10,11] II plt.show()	Name Size Type Date Modified Name Size Type Date Modified Image: Size File Folder 9/19/2019 11:02 AM Image: Size Size 9/19/2019 11:03 AM Image: Size Objets: Ever File 9/19/2019 5:10 SPM Size Objets: Ever File 9/19/2019 11:04 AM Image: Size Size 9/19/2019 11:04 AM Image: Size Size 9/19/2019 11:04 AM Image: Size Size 9/19/2019 11:05 PM Image: Size Size Size 9/19/2019 11:05 PM Image: Size Size Size Size Image: Size Size Size Size Image: Size Size Size Size Image: Size Size <th></th>	
	Permissions: RW End-of-lines: CRLE Encoding: ASCII Line: 19 Column: 1 Memory	83 %
	terresters into the case secondy being the in country.	

Figure 45 Specifying the x and v values in Matplotlib

We can add the grid by using the *plt.grid*(*True*).

🕏 Spyder (Python 3.6)	_	٥	×
File Edit Search Source Run Debug Consoles Projects Tools View Help	C:V KeersWCCL snuder-nv3		•
	File evolution		đΧ
Contemp.ov X test.tst X test.csv X Pandas.csv X	G O O		Q.
<pre>1 # Plotting using NutplotLib 1 # Plotting using NutplotLib 3 4 signort matplotLib.pyplot as plt 5 6 # we can specify x and y values and plot 7 vvalues = [2,4,5,6,7] 9 10 Xvalues, [2,4,5,6,7] 11 12 plt.plot(Xvalues, vvalues) 13 plt.grid(True) 14 plt.show() 16 17 18 19 20 </pre>	Name Size Type Date Modified > bistory_internat_py 68 bytes py File 9/19/2019 11:03 AM B history_internat_py 58 bytes py File 9/19/2019 11:03 AM D intory_phy 356 bytes py File 9/19/2019 11:03 AM D intory_phy 356 bytes py File 9/12/2019 11:03 AM D intorp_phy 356 bytes File 9/2/2019 51:0P M D intorbeip 0bytes cor File 9/19/2019 11:04 AM projet_ini.bak 21 KB ini File 9/19/2019 11:04 AM projet_ini.bak 21 KB ini File 9/19/2019 11:06 AM gryder.ini.bak 21 KB ini File 9/19/2019 11:06 AM gryder.ini.bak 21 KB ini File 9/19/2019 11:06 AM gryder.ini.bak 21 KB ini File 9/19/2019 11:09 PM gryder.ini.bak 31 bytes py File 9/19/2019 11:09 PM gryder.ini.bak 30 bytes cor File 9/19/2019 11:09 PM grytein.bak 30 bytes cor File 9/19/2019 11:09 PM grytein.console Hory bytes 9/19/2019 1:09 PM grytein.console Hory bytes 9/19/2019 1:09 PM		v v v
	remissions, we ind-or-lines; ckir incoding; ASCII line; 13 Column; 14	nemory: 64	

Setting of axis is done by using *plt.axis*([*xmin, xmax, ymin, ymax*])

Labels can be added to x and y axis using *plt.xlabel('X axis')* and *plt.ylable('Y axis')*

Title can be added using *plt.title('learning plotting in Python'*)

Legend can be set using the legend function *plt.legend()*

😵 Spyder (Python 3.6)		- 0	×
File Edit Search Source Run Debug Consoles Projects Tools View Help			
🗅 🖕 🕒 🐜 🧮 🖉 🕨 🛃 🍽 🗣 🔛 📫 🚝 🔶 📕 🔜 🔜 🔀 🗡 🦂	← → C:\Users\UCC\.spyder-py3	~ 🗲	• •
Editor - C:\Users\WCCspyder-py3\temp.py	X File explorer		đ×
T temp.pv 🔯 test.txt 🖾 test.csv 🖾 Pandas.csv 🖾	8 C O O		Q.
<pre>texture - (types you (type you (type you (type) you (type)) texture - (types you (type)) texture - (types you (type)) texture - (type you (type you (type)) texture - (type you (type you (type)) texture - (type you (type)) texture - (type you (type you (type you (type))) texture - (type you (type you (type)) texture - (type you (type you (type)) texture - (type you (type you (type you (type))) texture - (type you (type you (type you (type))) texture - (type you (type yo</pre>	Image by Determine Size Type Date Modified Name Size Type Date Modified Image by Determine Size File Folder 9/2/2019 5:12 PM Image by Determine Size File Folder 9/2/2019 5:16 PM Image by Determine File Folder 9/2/2019 5:16 PM Image by Determine File Folder 9/2/2019 5:16 PM Image by Determine File Folder 9/2/2019 5:11 PM Image by Determine File Folder 9/2/2019 5:11 PM Image by Determine Size File Folder Image by Determine Size File Folder Image by Determine Size by File 9/19/2019 1:103 AM Image by Determine Size by File 9/19/2019 1:103 AM Image by Determine Size File 9/2/2019 5:10 PM Image by Determine Distribution Size File 9/19/2019 1:103 AM Image by Determine 21 KB imin File 9/19/2019 1:103 AM Image by Determine 21 KB imin File 9/19/2019 1:103 AM Image by Determine 21 KB imin File 9/19/2019 1:103 AM Image by Determine 21 KB imin File 9/19/2019 1:103 AM Image by Determine 21 KB imin File 9/19/2019 1:103 AM Image by Determi		¢.
22 23 24 25 26	The explorer PW Ended liner (PLE Encoding ASCI) Line 20. Column 11	Memory 8	~

We save the plot by using the *plt.savefig('file name')*



2.3.2. Plot Types

There are several plot formats for visualizing information in Python such as Histogram, Scatter Plot, Bar Graph and Pie Chart. We will show here how to demand any and other plot format in Python.

1. Histogram

Histogram describes the information of a variable over a range of frequencies or values.



Figure 46 Plotting an Histogram in Python

2. Bar Graph

We create two arrays; the first array is the midpoint of the face of every bar i.e., where the midpoint of the bar graph should be. The second array is the height of the successive bar graph.



Figure 47 Bar graph in Python

We Can Plot a Dictionary Using Bar Chart





Figure 48 Plotting Bar graph from Dictionary

3. Pie Chart

Pie chart is used to compare multiple parts against the whole. For instance, let use a pie chart to visualize how a student spend her income.

Expenses	Amount
Food	5,000
Transport	1,500
Credit card	2,000
Accessory	500



Figure 49 Pie chart in Python

4. Scatter plot

Scatter plots displays the values for two sets of data, visualized as a collection of points.





Figure 50 Scatter plot in Python