

Shear Force and Bending Moment Diagram of Determinate Beams

1.0 General Background

1.1 Beam – structural member that carries load normal or perpendicular to its longitudinal axis




Figure 1

The action of the normal loads leads to the development of two types of response named (i) shear force and (ii) bending moments, at the cross section of the beam.


Unlike when beam is subjected to axial force where tensile and compressive stresses are developed, subjecting a beam to a load normal to its longitudinal axis led to the development of shear force and bending moments.

We shall know how to calculate and draw these stresses.

1.2 Types of Support in a Beam Structure


The supports in a beam supply the necessary reactive forces to maintain the structure in equilibrium as a result of applied load. These supports are:

- a) Fixed End / Bulk-In/ EnCastré/ Rigid



The support is capable of supplying three reactive forces: horizontal, vertical, and a fixing moment. This type of support is fixed so that it cannot rotate under the action of superimposed load.


Pin (or Hinged) Support



This is assumed to be free to rotate under the applied load, and can support two reactions. These are: horizontal and vertical forces.

c) The Roller Bearing

This can only supply one reaction. This is the case when a beam simply rests on a support




Roller Bearing Support

1.3 Types of Beams


Beams can be classified in many ways

i. Classification based on Support system:


a) Simply supported



b) Cantilever



c) Simply supported with overhangs



d) Proppped cantilever



e) Continuous



f) Fixed ends

ii. Classifications based of Method of Analysis

a) Determinate - can be analysed by the application of static equilibrium

For 2-dimensional beam structure

$$\begin{aligned}\sum F_y &= 0 \\ \sum F_x &= 0 \\ M_z &= 0\end{aligned}$$

For 3-dimensional beam structure

$$\begin{array}{ll}\sum F_x = 0 & \sum M_x = 0 \\ \sum F_y = 0 & \sum M_y = 0 \\ \sum F_z = 0 & \sum M_z = 0\end{array}$$

b) Indeterminate

can not be analysed by the application of static equilibrium



1.4 Types of Loads

Many forms of loads are dealt with in structural analysis. They include:

1. Static Load

i) Point Static


Also known as concentrated load



ii) Distributed Load (udl)


This is when a load is applied in such a way that it spread over the entire or part of its length.

- a. When the loading rate is uniform, it is called uniformly distributed load.




Uniformly distributed load (constant rate of loading)

- b. Triangular Load (varying rate of loading)




- c. Trapezoidal loaded (Varying rate of loading)



$$w \text{ KN/m (KN/m^2)}$$


- d. Irregularly loaded



$$w \text{ KN/m}$$

2. Dynamic Loads

These are moving loads. It usually occurs in highway/bridge analysis and design.




SHEAR FORCE AND BENDING MOMENTS

forces acting in a structural member may include some or all the following:


- Forces normal to elemental axis e.g. shear force.



- Forces parallel to elemental axis e.g. Axial or normal forces





- Bending Actions. For example, bending moment and twisting moment



In the beam type of structure, analysis involves the determination of the magnitude of the Shear force (SF) and the Bending moment (BM) at all points of the beam.

The Shearing Force

The shearing Force at any section of a beam is the tendency of the portion of the beam on one side of the section to slide or shear laterally relative to the other portion.



The Shearing force at any section is the algebraic sum of all the lateral components of the force acting on either side of the section.

The shearing force diagram is the one which shows the variation of shearing force along the length of the beam

Shearing force is +ve when the resultant to the left is upward, and -ve when resultant to the right is downward


Sending Moment

bending moment about any section is the algebraic sum of all the moments about that section of all the forces acting on either side of the section


The shearing force diagram is the one which shows the variation of shearing force along the length of the beam

Bending moment can be of two types:



- a. Sagging moment $\rightarrow +ve$



- b. Hogging moment $\rightarrow -ve$




Overall Diagram




The following examples will show how the SF and BM are calculated as well show how SF and BM diagrams are constructed for determinate beams.

Example 1



Draw the shear force and bending moment diagram for a simply supported beam with a point load as shown



Examp 2



Solution



$$\text{Total load} = wL \text{ kN}$$

$$\text{To find } R_A \approx R_B$$

$$\sum F_y = 0$$

$$R_A + R_B = wL \quad \rightarrow (1)$$

EMD (or fl)

$$-R_B L + wL \cdot \frac{L}{2} = 0$$

$$R_B L = \frac{wL^2}{2}$$

$$R_B = \frac{wL}{2} \text{ kN} \quad \rightarrow (2)$$

from eqn 1


$$R_A = wL - R_B$$

$$= wL - \frac{wL}{2}$$

$$= \frac{wL}{2} \quad \rightarrow (3)$$

Just one section is necessary

$$0 < x \leq L$$



S.F.

$$\sum F_y = 0$$

$$R_B - wx - F_{Ax} = 0$$

$$F_{Ax} = R_B - wx$$

$$= \frac{wL}{2} - wx \quad \rightarrow (4)$$

This is a general equation
at $x = 0$

$$F_{Ax=0} = \frac{wL}{2} - 0$$


$$= \frac{wL}{2} \text{ kN}$$

$$\text{at } x = L$$

$$F_{Ax=L} = \frac{wL}{2} - wL$$

$$= -\frac{wL}{2} \text{ kN}$$

$$3 \\ \angle x < 20^\circ$$



SF..

$$R_A - 5 - 2x + R_B - F(x) = 0$$

$$\begin{aligned} F(x) &= R_A + R_B - 5 - 2x \\ &= 16.67 + 28.33 - 5 - 2x \\ &= 45 - 5 - 2x \\ &= 40 - 2x \end{aligned}$$

$$\boxed{= 40 - 2x} \quad (6)$$

$$\text{at } x = 15 \text{ m}$$

$$\begin{aligned} F(x) &= 40 - 30 \\ &= 10 \text{ kN} \end{aligned}$$

$$\text{at } x = 20 \text{ m}$$

$$\begin{aligned} F(x) &= 40 - 40 \\ &= 0 \text{ kN} \end{aligned}$$

BM

$$\begin{aligned} R_A x - 5(x-5) - 2 \cdot x \cdot \frac{x}{2} + R_B(x-15) \\ - M(x) = 0 \end{aligned}$$

$$\begin{aligned} R_A x - 5x + 25 - x^2 + R_B x - 15R_B - M(x) \\ x(R_A - 5 + R_B) + 25 - 15R_B - x^2 = M(x) \\ 40x + 25 - 15 \cdot 28.33 - x^2 = M(x) \end{aligned}$$

$$40x - 399.95 - x^2 = M(x)$$

$$M(x) = -x^2 + 40x - 399.95$$

$$\text{at } x = 15 \text{ m}$$

$$\begin{aligned} M(x) &= -225 + 600 - 399.95 \\ &= 24.95 \text{ kN.m} \end{aligned}$$

$$\text{at } x = 20 \text{ m}$$

$$\begin{aligned} M(x) &= -400 + 800 - 399.95 \\ &= -99.95 \text{ kN.m} \end{aligned}$$

$$0.1 = W \sigma$$

$$= 0$$

$$M_x - Wx \cdot \frac{x}{2} - M_x = 0$$

$$M_x = R_A x - \frac{Wx^2}{2}$$

$$= \frac{Wlx}{2} - \frac{Wx^2}{2}$$

(2)

This is the B.M. expression & it is parabolic
at $x = 0$

$$M_{x=0} = \frac{Wl(0)}{2} - \frac{W(0)^2}{2}$$
$$= 0 \text{ kNm}$$

At $x = L$

$$M_{x=L} = \frac{WL}{2} - \frac{WL^2}{2}$$
$$= 0 \text{ kNm}$$

For a singly supported beam carrying a w/l, the
relationship between the SF & BM is that at
the point of zero shear, the BM is maximum

$$F = \frac{dM}{dx} \Rightarrow$$


$$= R_A - Wx$$

$$= 0$$

$$x = \frac{R_A}{W} = \frac{\frac{wl}{2}}{W} = \frac{l}{2} \text{ m}$$

with w.s.a
down max

$$\begin{aligned}
 &= R_A \frac{w(L-s)}{L} \\
 &= 0 \\
 &= s \\
 M_{x=s} &= \frac{w(L-s)s}{L} \\
 &= \frac{ws(L-s)}{L}
 \end{aligned}$$



$$\begin{aligned}
 f_y &= 0 \\
 R_A - W &= 0 \\
 F_x &= R_A - W \\
 &= \frac{ws}{L} - R_A \\
 &= \frac{ws}{L} - \frac{ws}{L} \\
 &= 0
 \end{aligned}$$

$$= -\frac{ws}{L}$$

so express. It is the

$$x = 0$$

$$F_x = -\frac{ws}{L}$$

$$F_{x=L} = -\frac{ws}{L}$$

BM

$$\begin{aligned}
 R_A x - w(x-s) - M_{x=s} &= 0 \\
 M_x &= R_A x - w(x-s) \\
 &= \frac{w(L-s)x}{L} - w(x-s) \\
 &= wx - \frac{wsx}{L} - wx + ws \\
 &= -\frac{wsx}{L} + ws
 \end{aligned}$$

This is the BM expression at $x = s$

$$\begin{aligned}
 M_{x=s} &= -\frac{ws^2}{L} + ws \\
 &= ws\left(1 - \frac{s}{L}\right) \\
 &= ws\frac{(L-s)}{L}
 \end{aligned}$$

at $x = L$




$$M_{x=L} = -\frac{wsL}{L} + ws$$

$$= -ws + ws$$

$$= 0 \text{ kNm}$$

Conclusion:
For simply supported beam it point load.

Solution



\leftarrow Reaction at B

\Rightarrow

$$+ R_B = W \quad \rightarrow \textcircled{1}$$

$$0 + Ws = 0 \quad \rightarrow \textcircled{2}$$

$$R_B L = Ws$$

$$R_B = \frac{Ws}{L} \quad \rightarrow \textcircled{2}$$

from eqn 1

$$R_A = W - R_B$$

$$= W - \frac{Ws}{L}$$

$$= W \left(1 - \frac{s}{L}\right) \quad \rightarrow \textcircled{3a}$$

$$= W \frac{(L-s)}{L} \quad \rightarrow \textcircled{3b}$$

Section $\Rightarrow 0 \leq s \leq L$



SF

$$\sum F_y = 0$$

$$R_A - F_x = 0$$

$$F_x = R_A$$

$$= \frac{W(L-s)}{L}$$

This is the general eqn of SF for the section constant w.r.f. force at $x = 0$; $F_0 = W \frac{(L-s)}{L}$

$$\text{at } x = s \quad F_s = W \frac{(L-s)}{L}$$

BM

$$\sum M = 0$$

$$R_A x - M_x = 0$$

$$M_x = R_A x \frac{W(L-s)x}{L}$$

$$x - 2x \cdot \frac{x}{2} - M_{(x)} = 0$$

$$(2) = R_A x - x^2$$

$$\boxed{= 16.67x - x^2} \quad (3)$$

$$+ x = 0$$


$$M_{(x)} = 0$$

$$\text{at } x = 5 \text{ m}$$

$$M_{(x)} = 16.67 \times 5 - (5)^2$$

$$= 83.35 - 25$$

$$= 58.35 \text{ kN.m}$$



S.F.

$$R_A - 2x - 5 - F(x) = 0$$

$$F(x) = R_A - 2x - 5$$

$$= 16.67 - 2x - 5$$

$$\boxed{= 11.67 - 2x} \quad (4)$$

$$\text{at } x = 5 \text{ m}$$

$$F(x) = 11.67 - 10$$

$$= 1.67 \text{ kN}$$

$$x = 15 \text{ m}$$

$$F(x) = 11.67 - 2 \times 15$$

$$= 11.67 - 30$$

$$= -18.33 \text{ kN}$$

At point where S.F. = 0
Eqn 4 = 0
that is

$$11.67 - 2x = 0$$

$$2x = 11.67$$

$$\boxed{x = 5.84 \text{ m (F.S. left)}}$$

B.M

$$R_A x - 5(x-5) - 2x \cdot \frac{x}{2} - M_{(x)} = 0$$

$$M_{(x)} = R_A x - 5x + 25 - x^2$$

$$= 16.67x - 5x + 25 - x^2$$

$$= 11.67x + 25 - x^2$$

$$\boxed{= -x^2 + 11.67x + 25} \quad (5)$$

$$\text{at } x = 5 \text{ m}$$

$$M_{(x)} = -25 + 58.35 + 25$$

$$= 58.35 \text{ kN.m}$$

$$\text{at } x = 15 \text{ m}$$

$$M_{(x)} = -(15)^2 + 175.05 + 25$$

$$= -225 + 175.05 + 25$$

$$= -24.95 \text{ kN.m}$$


Max moment at $x = 5.84$

$$M_{\max} = -(5.84)^2 + 11.67 \times 5.84 + 25$$




$$= -34.11 + 68.15 + 25$$

$$\boxed{= 59.54 \text{ kN.m}}$$

file 6



solution



Find the reactions R_A & R_B

$$R_A + R_B - 2 \times 20 - 5 = 0$$

$$R_A + R_B = 45 \quad \text{--- (1)}$$

M_A

$$-15R_B + 5 \times 5 + 2 \times 20 \times \frac{20}{2} = 0$$

$$-15R_B + 25 + 400 = 0$$

$$15R_B = 425$$

$$R_B = 28.33 \text{ kN}$$

from eqn 1

$$R_A = 45 - R_B$$

$$= 45 - 28.33$$

$$= 16.67 \text{ kN}$$


Sections

$$(1) 0 < x < 5$$

$$(2) 5 < x < 15$$

$$(3) 15 < x < 20$$

$$(1) 0 < x < 5$$



S.F.

$$R_A - 2x - F(x) = 0$$

$$F(x) = R_A - 2x$$

$$= 16.67 - 2x \quad (2)$$

$$\text{at } x = 0$$

$$F(x) = 16.67 \text{ kN}$$

$$x = 5$$

$$F(x) = 16.67 - 2 \times 5 = 6.67 \text{ kN}$$

$$G = 18.33x - 2x^2$$

$$2x = 0$$

$$(x=0) = 0 \text{ kN.m}$$


$$x = 5$$

$$(x=5) = 18.33 \times 5 - (5)^2$$

$$= 91.65 - 25$$

$$= 66.65 \text{ kN.m}$$

$$5 \leq x \leq 15$$



E:

$$\sum F_y = 0$$

$$R_A - 2x - 5 - F(x) = 0$$

$$F(x) = R_A - 2x - 5$$

$$= 18.33 - 2x - 5$$

$$= 13.33 - 2x \quad \textcircled{*}$$

$$\text{at } x = 5$$

$$F(x=5) = 13.33 - 2 \times 5$$

$$= 13.33 - 10$$

$$= 3.33 \text{ kN}$$

$$\text{at } x = 15$$

$$F(x=15) = 13.33 - 2 \times 15$$

$$= -16.67 \text{ kN}$$

At the point where S.F crosses the axis, Σ

$$F(x) = 0$$

that is

$$0 = 13.33 - 2x$$

$$x = 6.67 \text{ m. from A}$$

BM

$$\Sigma M_A = 0$$

$$R_A x - 2x \cdot \frac{x}{2} - 5(x-5) - M(x)$$

$$M(x) = R_A x - x^2 - 5x + 25$$

$$= 18.33x - 2x^2 - 5x + 25$$

$$= -2x^2 + 13.33x + 25$$

$$\text{at } x = 5$$

$$M(x=5) = -(25) + 66.65 + 25$$

$$= 66.65 \text{ kN.m}$$

$$\text{at } x = 15$$

$$M(x=15) = -225 + 199.95 + 25$$

$$= 0.05 \text{ kN.m}$$

$$\approx 0.1 \text{ kN.m}$$


The max Moment at

$$x = 6.67 \text{ m}$$

$$M_{\max} = -(44.85) + 88.91 + 25$$

$$= 69.42 \text{ kN.m}$$

(9) -



$$R_A + R_B = 5 + 2 \times 15 \\ = 5 + 30 \\ = 35 \Omega \quad \text{--- (1)}$$

about a

$$5 \times 5 + 2 \times 15 \cdot \frac{15}{2} - 15R_B = 0$$

$$15R_A = 25 + 225 = 250$$

$$R_B = 16.67 \text{ kN}$$

from eqn 1

$$R_A = 35 - 16.67 \\ = 18.33 \text{ kN}$$

A free body diagram of a beam segment. At the left end, there is a vertical reaction force labeled \$R_A\$ pointing upwards. At the right end, there is a horizontal reaction force labeled \$S.F.\$ pointing to the right. A coordinate system is established at the left end, with the horizontal axis labeled \$x_1\$ pointing to the right and the vertical axis labeled \$y_1\$ pointing upwards.

58

$$\sum F_y = 0$$

$$R_A - 2x - F_{(2)} = 0$$

$$F(x) = R_A - 2x$$

$$= 18.33 - 2x \quad (2)$$

$$at x = 0$$

$$F(x=9) = 18.33 \text{ kN}$$

at $x = 5$


$$F(x=5) = 18.33 - 2 \times 5 \\ = 8.33 \text{ kN}$$

BM



$$R_A x - 2x \cdot \frac{x}{2} - M(x) = 0$$

$$M(x) = R_A x - x^2$$


ple 4



Ans



$$0 < x < l$$



S.F

$$\sum F_y = 0$$

$$F_{(x)} - WL = 0$$

$$F_{(x)} = WL$$

This is a linear function of x
at $x = 0$

$$F_{(x=0)} = w \times 0 = 0 \text{ KN}$$

$$\text{at } x = L$$

$$F_{(x=L)} = WL$$

$$= wl \text{ KN}$$

B.M

$$\sum M_{(x)} = 0$$

$$-M_{(x)} + WL \cdot \frac{x}{2} = 0$$

$$M_{(x)} = WL \frac{x^2}{2}$$

A quadratic expression


$$\text{at } x = 0$$

$$M_{(x=0)} = 0 \text{ KN.m}$$


$$\text{at } x = L$$

$$M_{(x=L)} = WL \frac{L^2}{2}$$


$$= \frac{wl^2}{2} \text{ KN.m}$$



Int. on



Only one section will
be cut referred at RHS.



$$\sum F_y = 0$$

$$F - W = 0$$

$$F(x) = W \quad \text{---} \quad (1)$$

That is, independent of the beam span. Constant force
at the length

$$\text{at } x = 0$$

$$F(x=0) = W \text{ kN}$$

$$\text{at } x = l$$

$$F(x=l) = W \text{ kN}$$

B.M

$$\sum M_x = 0$$

$$WX - M_x = 0$$

$$M(x) = WX$$

A func of x .

$$\text{at } x = 0$$

$$M(x=0) = W \times 0$$

$$= 0 \text{ kNm}$$

$$\text{at } x = l$$

$$M(x=l) = WL$$

$$= WL (\text{kNm})$$

(6)

$$P.L = W \cdot$$

The BM at. $x = \frac{L}{2}$

$$M(x=\frac{L}{2}) = \frac{WL\frac{L}{2}}{2} - W(\frac{L}{2})^2$$

$$= \frac{WL^2}{4} - \frac{WL^2}{8}$$

$$= \frac{WL^2}{8}$$
 kN.